

Silkolene[®]

SILKOLENE PRO FST

Fuel system treatment for petrol engines

Description

SILKOLENE PRO FST is a multi-functional fuel treatment. It protects against cold start wear, protects the fuel system from corrosion and keeps the injectors; intake systems and carburettors free from deposit build up ensuring optimum performance. It is very effective against carburettor icing in low temperature environments, and combats starting problems, stalling and rough running at low engine revs.

Application

SILKOLENE PRO FST can be used in leaded and unleaded fuel and in both 2 and 4-stroke engines. It reduces the incidence of pre-ignition and also enhances the fuel's octane rating to a small extent.

Recommended mix ratio:-

SILKOLENE PRO FST is recommended to be used at a concentration of 1% to 2%

For 1% mix 100 parts fuel to 1 part PRO FST

For 2% mix 50 parts fuel to 1 part PRO FST.

Advantages

- Multifunctional performance, wear protection, deposit protection and corrosion protection
- SILKOLENE PRO FST is compatible with catalytic converters
- Synthetic ester technology provides protection to metallic parts of the engine where the lube oil cannot reach
- Provides protection during periods of inactivity

Updated 25/10/2018 AB



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products